


ALBAU SIA

Technical data sheet

BL-V / SINGLE-SIDED SELF-ADHESIVE SEALING TAPE

Foamed polyethylene single-sided self-adhesive sealing tape for internal noise elimination





| Brand | Albau | | | |
|--------------------------|--|--|--|--|
| Suitable for | Joints of load-bearing profiles for drywall construction | | | |
| Tape material | Foamed polyethylene | | | |
| Roll length | 30 m | | | |
| Tape thickness | 3 mm | | | |
| Density | $29 \pm 5 \text{ kg/m}^3$ | | | |
| Temperature resistance | -40°C to +80°C | | | |
| Tensile strength | 790 kPa lengthwise | | | |
| | 370 kPa crosswise | | | |
| Max. elongation | 130 % lengthwise | | | |
| | 190 % crosswise | | | |
| Compression set | 0,5 h after discharge: 24 % | | | |
| | 24 h after discharge: 17,6 % | | | |
| Fire resistance | B2 according to DIN 4102 on metallic or mineral | | | |
| | substrates | | | |
| Water absorption | max. 1% | | | |
| Water vapor permeability | 9,2 x 10-9 kg/(m ² .s) | | | |
| Joint sound reduction | Rs,w (C; Ctr) = 65 dB | | | |
| Color | Anthracite | | | |



Features:

- Especially suitable for joints of load-bearing profiles for drywall construction
- Reduces sound transmission within the structure
- Compensates unevenness of profiles
- Easy application thanks to the self-adhesive layer

Installation instructions:

- Clean the surface to which the tape is to be bonded from dust and other separating agents
- Remove the protective foil from the self-adhesive layer and bond the tape to a profile
- Mount another profile through the tape.

Packaging, storage and transport:

- Store in a dry roofed place
- Transport and store at $+5^{\circ}\text{C} \sim +40^{\circ}\text{C}$
- Max. storage time 1 year

Certification and standards:

The product is not subject to any harmonized standard

| Product code | EAN | Tape width | Rolls in transport package | Rolls on palette |
|--------------|---------------|------------|----------------------------|------------------|
| ALB-BL-V-30 | 4752265008289 | 30 mm | 30 pcs. | 360 pcs. |
| ALB-BL-V-50 | 4752265008296 | 50 mm | 18 pcs. | 216 pcs. |
| ALB-BL-V-70 | 4752265008302 | 70 mm | 12 pcs. | 144 pcs. |
| ALB-BL-V-90 | 4752265008319 | 90 mm | 10 pcs. | 120 pcs. |