

	ALBAU SIA
	Technical data sheet

EXPANDING UNIVERSAL SEALING TAPE

Expanding universal sealing tape can be universally used for sealing joints in buildings. The joint sealing tape is made from flexible polyurethane foam with acrylate dispersion impregnation, auxiliary materials and filler substances. Pre-compressed rolled goods with acrylate contact adhesive as installation aid



Application:

- Window and door frame gaps
- Joints between masonry or concrete element parts
- Joints in roof constructions, roof windows
- Connection and expanding joints between different building construction components
- New constructions and renovation projects
- Provides sound and vibration isolation caused by ventilation equipment

Brand		Albau
Color		Grey
Construction materials class	DIN 4102	B1
Air permeability	EN 1026	$an < 1 \text{ m}^3 / (\text{h m dPa}^2/3)$
Driving rain resistance	EN 1027	$\geq 600 \text{ Pa}$
Compatibility with neighbouring construction materials	DIN 18542	Passed
Water vapour diffusion	EN ISO 12572	$sd < 0,5 \text{ m}$
Emissions	GEV	EMICODE® EC 1 PLUS
Temperature resistance	DIN 18542	80°C
Application temperature range		- 30°C to 100°C
Storage stability		18 months from the production date

Product code	EAN	Nominal joint width mm	Joint depth mm	Roll length m	Rolls in package pcs.
ALB-PU-2-4-10	4752265004823	2-4	>10	24	30
ALB-PU-3-7-15	4752265004830	3-7	>1R5	15	20
ALB-PU-4-9-15	4752265004847	4-9	>15	15	20
ALB-PU-5-12-20	4752265004854	5-12	>20	10	15
ALB-PU-7-15-20	4752265004861	7-15	>20	7,5	15

MADE IN EU

Distributor: SIA "Albau" – Tīnužu šoseja 21, Ikšķile, district Ogre, LV-5052, Latvia,
Reg.Nr.40103561205 www.albau.eu www.xbau.eu

