
	ALBAU SIA	V 03
	Product technical data sheet	v1
		Page 1
		Pages 1

PJ 12F L / Plasterboard edging profile with dilatation tape and protective lip



SKU	Bar code	Material	Width	Length	Amount in a transport package
ALB-PJ-12F-L-25	4752265004557	PVC	12,5 mm	2,5 m	50 pcs.

Application: creates a perfect finish and flexible joint between 12,5 mm plasterboard and window, door frames.

Advantages:

- The lip on the visible face of the bead creates an aesthetically neat and smooth connection between the plasterboard and the frame;
- The lip prevents dust and dirt from settling on the flexible PE tape.

Recommendations:

- Remove the protective plastic sheet from the window or door frame.
- The frame surface must be levelled, dry and free of all dust, dirt and grease.
- Use the scissors for working with plastic beads to shorten a bead.
- After fitting a bead to the edge of the plasterboard, remove approx. 3 cm of backing from the dilatation tape.
- Fit the plasterboard into its required position and carefully remove the backing from the entire bead. Gradually press the board firmly to the frame, along its entire length.
- Then screw the board to the jamb and head.
- Installation work must take place within a temperature range of +5°C to +35°C.

Storage:

- Store in a horizontal position.
- The profiles packed in cardboard boxes must be stored in a dry environment.
- Maximum recommended storage period is 18 months.



MADE IN EUROPE

Distributor: Albau SIA – 20k-1-14, Talivalza street, Riga, LV-1006, Latvia, Reg.No. 40103561205



www.albau.eu



www.xbau.eu