

TECHNICAL DATA SHEET

3688 WASHI-TEC®- Masker

Pre-taped drop film with washi masking tape for indoor and outdoor application.

Properties

- High quality masking tape combined with environmental friendly and static charged PE film
- UV resistant
- Sharp painting lines

Area of Use

- Efficient covering and masking of large surfaces (walls, windows, floors, furniture) and crips paint lines in one step

Technical Data

- Backing: Washi, UV resistant
- Thickness: 0,08 mm
- Adhesive: acrylic
- Adhesion to Stainless Steel : 1,1 N / 10 mm
- Tensile: 33,9 N / 10 mm
- Elongation: 4%
- Film: PE, static charged
- Thickness Film: 8 μ



3 months



4 weeks



100 °C

Application	Fitness
Indoor	●●●
Outdoor	●
Sensitive Surfaces	●●
Finished wood	●●
PVC	●●
Finery, Stone, Concrete*	●
Remarks	

* Do not use on marble, natural stone and terra-cotta.

● good ●● better ●●● best

Physical and technical data displayed in this document are based on international accepted test methods but are no guarantee for product characteristics or product performance. Individual roles may vary slightly from these averages. The user should determine whether a product is fit for a particular purpose and is suitable for the user's method of application before use.