



## **ALBAU SIA**

#### **Technical data sheet**

# **CORNER PROFILE**

Corner profile made from steel with special anti-corrosion coating for creating precise corners when plastering in the interior - the shape of profile enable creation of slightly round edges





Brand	Albau		
Suitable for	Interior use, all types of cement-based plasters		
For plaster thickness	6 mm		
Profile material	Steel with special corrosion protection		
Profile material thickness	0,45 mm		
Profile length	2000 mm; 2500 mm; 3000 mm		
Arm width	32 x 32 mm		

## **Features:**

- With corrosion protection the profile is coated with anti-corrosion coating, which differs from conventional zinc by the addition of other elements, especially magnesium. This enrichment increases the corrosion resistance of the sheet and allows the thickness of the coating to be reduced while maintaining or increasing the corrosion protection compared to conventional materials
- Minimizes the time required to create a perfect corner
- Protects the area where the plaster is most vulnerable
- For all types of cement-based plasters
- For plaster thickness of 6 mm
- Not suitable for use with gypsum-based plasters



## **Application:**

- Before starting plastering, it is necessary to level the profile to the correct position using a spirit level
- There are several methods for fixing the moulding to the corner: mechanically (nails, staples) or mounted on mortar or special adhesive
- The grid ensures the connection to the plaster and the seating of the moulding as required, thereby the appearance of even inaccurately executed corners can be adjusted

## Packaging, storage and transport:

- Packed in carton boxes
- Store in a dry roofed place
- Transport and store in horizontal position

#### **Certifications and marks:**

The product is not subject to any harmonized standard

Product code	EAN	Profiles in transport package, pcs.	Profiles on pallet, pcs.
ALB-PSC-045ZN-20	4752265007220	25 (50m)	6250 (12500m)
ALB-PSC-045ZN-25	4752265007237	25 (62,5m)	5750 (14375m)
ALB-PSC-045ZN-30	4752265007244	25 (75m)	4750 (14250m)