



Technical data sheet

347 / Barrier tape FLEX

Kip® 347 barrier tape is a special adhesive tape designed for permanently and airtight sealing cracks and openings around pipes, chimneys, rafters, roof windows, etc. Ideal for new and retrofit insulation projects where permanent airtight joints are required



| | |
|-----------------------------------|--------------------|
| Brand | Kip |
| Suitable for | Indoor use |
| Surface | Different surfaces |
| Duration of use | Permanent |
| Tape material | HDPE |
| Adhesive | Acrylate |
| Roll length | 25 m |
| Tape width | 60 mm |
| Tape thickness | 0,30 mm |
| Temperature resistance | -40 to 70° C |
| Adhesion strength to steel | 13,5 N/10mm |
| UV resistance | 6 months |

Features and benefits:

- Single-sided adhesive tape
- Made from a reinforced, highly flexible HDPE film
- Very high adhesive strength on a variety of surfaces, even at low temperatures, thanks to the thick adhesive coating
- Also sticks to slightly damp surfaces (e.g. condensation moisture)
- Temperature resistant
- Very resistant to aging

| Product code | EAN | Dimensions | Amount of products in transport packaging, pcs |
|--------------|---------------|--------------|--|
| KIP-347-60 | 4013142347601 | 60 mm x 25 m | 10 |