



RT-SDSB Brickdrill SDS plus

Drill bits for fast drilling in ceramic materials without damage BRICKDRILL SDS plus



Product information

Features and benefits

- Tip angle 120° allows for fast drilling of holes in ceramic material without damage
- Short drill bit flute accelerates dust extraction between the slots of ceramic brick
- Drilling without hammering
- Perfect straight hole without damaging the ceramic brick
- Steel on the specification of 34CrNiMo6 provides high resistance and durability
- Subjected to a heat treatment by which the hardness of the steel increases to 52 HRC for optimal resistance during drilling
- Also suitable for aerated concrete
- Long drill bit shank allows to drill deep holes also by insulation
- Extremely high durability confirmed by the international certificate SicherSafe

Suitable for

- Hollow Brick
- Aerated Concrete Block

Applications

- Drilling in ceramic hollow bricks
- Suitable for use with SDS plus Rotary Hammer

Certificate



Recommended fasteners

- 4ALL UNIVERSAL PLUG
- R-KEM II with Threaded Rods for Masonry
- FF1-N FRAME FIXING COUNTERSUNK - DELTA TONE
- TFIX-8M Facade fixing with metal nail

RT-SDSB Brickdrill SDS plus

Product information

Attention



Technical Data

Index	Ø	L	Working length	Quantity	EAN	Box weight	Outer weight
	[mm]	[mm]	[mm]	[pcs]		kg	kg
RT-SDSB-6/260	6	260	200	1	5906675046303	0.30	0.30
RT-SDSB-8/260	8	260	200	1	5906675046310	0.30	0.30
RT-SDSB-8/310	8	310	250	1	5906675047553	0.30	0.30
RT-SDSB-8/460	8	460	400	1	5906675047553	0.20	20.00
RT-SDSB-10/260	10	260	200	1	5906675046334	0.30	0.30
RT-SDSB-10/310	10	310	250	1	5906675047560	0.30	0.30
RT-SDSB-10/460	10	460	400	1	5906675047560	0.20	20.00
RT-SDSB-12/260	12	260	200	1	5906675046341	0.30	0.30
RT-SDSB-15/260	15	260	200	1	5906675046358	0.30	0.30
RT-SDSB-16/260	16	260	200	1	5906675046365	0.30	0.30