

SLAM+

ERGONOMICAL!

Inspired from the SLAM model, SLAM + offers even greater comfort thanks to its stylish twin-material, ergonomic temples.

 PLATINUM



SLAPPSI



SLAPCSP



SLAPPSF


27 g

+ COMFORT, TWIN MATERIAL BLACK AND ORANGE TEMPLES

+ ALL-ROUND VISION

+  PLATINUM (+P) COATING

+ ADJUSTABLE STRAP IN OPTION

bolle
SAFETY

SLAM+

ERGONOMICAL!

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
SLAM+	 Clear	SLAPPSI	2C-1,2  1 FT KN C€	 EN166 1 FT C€	Anti-scratch/anti-fog/ 
	 CSP	SLAPCSP	5-1,4  1 FT KN C€	 EN166 1 FT C€	Anti-scratch/anti-fog/ 
	 Smoke	SLAPPSF	5-3,1  1 FT KN C€	 EN166 1 FT C€	Anti-scratch/anti-fog/ 

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles (optional).

N. Resistance to fogging (optional).

C€ European standard  Manufacturer name

TECHNOLOGY

CSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments. CSP is also combined with the exclusive PLATINUM coating that sustainably combats fogging.

PLATINUM

The new exclusive scratch and fog resistant coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

PACKAGING AND EAN13 CODE

	SLAPPSI	SLAPCSP	SLAPPSF
Individual plastic bag	3660740007492	3660740007515	3660740007508
10 safety spectacles per inner box	3660740107499	3660740107512	3660740107505
200 safety spectacles per outer pack	3660740207496	3660740207519	3660740207502

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

C€ European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS

LENSES	PC - 2,3 mm - Curve 11
FRAME	Non applicable
TEMPLES	PC/TPR
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No



Non-binding visual

25/08/2014

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY