

	ALBAU LTD	V 03
	Product technical data sheet	v1
		Page 1
		Pages 1

PC U R250 / Flexible, universal corner profile (without mesh)



Application: Universal corner profile can be used for all types of angles – both inner and outer ones. Used in risky joints of drywall constructions. Protects corners against mechanical damage and prevents the small crack formation. Creates an aesthetically perfect finish.

Advantages:

- Joint duration;
- Flexible setting of angle
- It is the solution of cracking problem (dilatation) and additional reparations;
- Universal size;
- Used in risky joints of plaster board constructions (sloping edge + ceiling, forward wall + sloping edge).

Technical data:

Product code	EAN	Material	Size	Length	Package
ALB-PC-U-R250	4751023401539	PVC	52 mm	25 m	1 pcs.

Installation tips:

- Recommended clip on distance is 10 cm;
- To shorten the profile use scissors designed for work with plastic profiles.

Storage:

A horizontal storage position is recommended. The profiles need to be stored in a dry place the temperature range of -5°C to +40°C. Maximum recommended storage time is 24 months.



MADE IN EUROPE

Distributor: Ltd "Albau" – Ritvari, Rumbula, Stopinu district, LV-2121, Latvia. Reg.No. – 40103561205

www.albau.eu

www.xbau.eu