

## Raised csk head, PZ, blue zinc-plated



### BUILDING MATERIALS

- Glued-laminated timber
- Cross-laminated timber
- Laminated veneer plywood panels (e.g. Multiplex)
- Hard woods (pre-drilled)
- Chipboards and oriented strand boards (e.g. OSB panels)
- Plywood
- Solid wood panels
- Soft woods
- And many other wood materials

### ADVANTAGES/BENEFITS

- The unique Power-Fast thread reaches into the screw tip and ensures a fast bite. This makes your work noticeably easier with all wood materials.
- The shank ribs (for screws with partial thread from 50 mm in length and up) substantially reduce drive-in resistance and thus enable greater power and battery conservation in your work.
- The optimised head geometry enables an exact and splinter-free surface finish without the screw twisting off, even with connections close to the edge.
- The ETA approval guarantees the high safety standard and the premium quality of fischer Power-Fast screws.

### APPLICATIONS

- General wood joints
- Finger tightening elements
- Safety-relevant applications
- Plankings
- Skirting
- Door and metal fittings

### APPROVALS



### FUNCTIONING

- Screws with partial threads can lock wood parts into place by tightening them against each other.
- Full-thread screws are recommended for mounting thin parts and in less firm wood materials (e.g. soft woods).
- Screws with countersunk head can be flush mounted with the wood.
- Pan-Head screws are particularly well suited for metal and wood joints.
- The raised countersunk head is particularly suitable for joints where the screw head is visible and needs to leave behind an attractive appearance.

### TECHNICAL DATA



FPF-LZ ZPF

**Diameter 3,5**

Diameter	Length	Drive	Art.-No.		ETA-approval	Full thread length	Sales unit
d	l					l <sub>g</sub>	
[mm]	[mm]		Art.-No.	Article name		[mm]	[pcs]
3,5	16	PZ2	<b>652519</b>	<b>FPF-LZ 3,5 x 16 ZPF 500</b>		12	500

## Diameter 4,0

Diameter d [mm]	Length l [mm]	Drive	Art.-No.  Art.-No.	Article name	ETA-approval	Full thread length l <sub>g</sub> [mm]	Sales unit  [pcs]
4,0	20	PZ2	<b>652525</b>	<b>FPF-LZ 4,0 x 20 ZPF 500</b>	■	15	500
4,0	30	PZ2	<b>652527</b>	<b>FPF-LZ 4,0 x 30 ZPF 500</b>	■	25	500
4,0	35	PZ2	<b>652528</b>	<b>FPF-LZ 4,0 x 35 ZPF 500</b>	■	30	500
4,0	45	PZ2	<b>652530</b>	<b>FPF-LZ 4,0 x 45 ZPF 500</b>	■	40	500

**Diameter 5,0**

Diameter	Length	Drive	Art.-No.		ETA-approval	Full thread length	Sales unit
d	l					l <sub>g</sub>	
[mm]	[mm]		Art.-No.	Article name		[mm]	[pcs]
5,0	60	PZ2	<b>652543</b>	<b>FPF-LZ 5,0 x 60 ZPF 200</b>		54	200