

Collomix®

Rotary mixer AOX-S Lump free and quickly mixed



45.499



- For mixing volumes of up to 40 litres ready-mix; suitable for mortar, screed, plaster, tile adhesives, etc. (mixing tool KR); Thin-bed mortar, self-leveling compound, Pointing mortar, etc. (Mixing tool DLX)
- high-speed mixing tool for lump free intermixing
- Mixing action via rotating tub
- Edge and bottom scraper
- Safety cut-off
- compact and mobile
- 2 interchangeable mixing tools (KR & DLX)

Technical data AOX-S	
Size of mixing tub:	65 Ltr.
Max. effective volume:	max. 40 litres
Power rating of mixing mechanism:	1,0 kW / 230 V
RPM of mixing mechanism:	750 min ⁻¹
RPM of tube drive:	18 min ⁻¹
Dimensions (l x w x h):	60x82x87
Weight:	51 kg

Consistency range: very stiff to plastic		
Material (weight without added water):	DLX	KR
Slightly moist concrete with grain size of -8 mm (30 l)	-	+
Concrete with max. grain size of 8 mm (30 l)	-	+
Cement screed (35 l)	-	+
Universal mortar (40 l)	-	+
Gypsum-lime mortar (35 l)	-	+
Light wall mortar (25 l)	-	+
Cement stucco (40 l)	+	+
Gypsum plaster (40 l)	+	+
Loam plaster without fiber (40 l)	+	+
Heat-insulating plaster (30 l)	-	+
Mortar for natural stone slabs (30 l)	-	+
2-component slab pointing mortar (-1,2 mm, 30 l)	+	+
Middle-bed mortar (25 l)	-	+
Tile adhesives (flexible mortar, 25 l)	-	+
Pointing mortar (25 l)	+	+
Consistency range: soft to spreading		
Pouring screed (40 l)	+	+
Soft/spreading types of mortar (40 l)	+	+
Thin-bed mortar, cement for concrete precision blocks (30 l)	+	+
Creamy types of plaster (40 l)	+	+
Adhesive grouting compounds as backing for plaster (30 l)	+	+
Tile adhesives (25 l)	+	+
Pointing mortar (25 l)	+	+
Joint cements (30 l)	+	+
Adhesive grouting compounds as backing for panels/tiles (30 l)	+	+
2-component sealing grouting compounds (25 l)	+	+
Leveling compounds (25 l)	+	+
2-component epoxy-resin and sand mix (30 l)	+	+
+ = suitable - = unsuitable		



QR-Code: Application video



Practical accessory: Trolley

Your Collomix dealer: