



ColloMatic® -

Rotary tub mixer AOX-S / POX-S

Versatile – practical – comfortable

Compact mixer for use on site



- **Effective mixing** without tying anyone down
- **Two models** for many different types of materials
- **Powerful drive** for lump-free mixing of for mixing loads up to max. 40 litres.
- **Rotary table with its own motor** for an optimum mixing process and shorter mixing times
- **Edge scraper** prevents sediment on the edges of the container
- **Safety:** The mixing tool is covered by a guard hood. A safety switch stops the mixing tool on opening.
- **Rugged tub** made of high-strength PE material with reinforced recessed handles for transportation and recessed holders in the base to prevent the tub from slipping.
- **Highly mobile:** Light-weight and with a practical handle to enable the machine to be moved around easily.



bricklayers • plasterers • stuccoists • painters • tilers • screed layers

Collomix®

Collomix Rühr- und Mischgeräte GmbH

Mixing material and recommended quantities

Consistency range: very stiff to plastic

Material (weight without added water):	AOX/DLX	AOX/KR	POX
Slightly moist concrete with grain size of -8 mm (30 l)	-	+	+
Concrete with max. grain size of 8 mm (30 l)	-	+	+
Cement screed (35 l)	-	+	+
Synthetic resin screed (30 l)	-	+	-
Universal mortar (40 l)	-	+	+
Gypsum-lime mortar (35 l)	-	+	-
Light wall mortar (25 l)	-	+	+
Stucco mortar (30 l)	+	+	-
Cement stucco (40 l)	+	+	+
Gypsum plaster (40 l)	+	+	-
Loam plaster without fiber (40 l)	+	+	-
Heat-insulating plaster (30 l)	-	+	+
Air-entrained light exterior plaster (30 l)	-	+	+
Mortar for natural stone slabs (30 l)	-	+	+
2-component slab pointing mortar (-1,2 mm, 30 l)	+	+	-
Middle-bed mortar (25 l)	-	+	-
Tile adhesives (flexible mortar, 25 l)	-	+	-
Pointing mortar (25 l)	+	+	-

Consistency range: soft to spreading

Pouring screed (40 l)	+	+	-
Soft/spreading types of mortar (40 l)	+	+	-
Thin-bed mortar, cement for concrete precision blocks (30 l)	+	+	-
Creamy types of plaster (40 l)	+	+	-
Adhesive grouting compounds as backing for plaster (30 l)	+	+	-
Tile adhesives (25 l)	+	+	-
Pointing mortar (25 l)	+	+	-
Joint cements (30 l)	+	+	-
Adhesive grouting compounds as backing for panels/tiles (30 l)	+	+	-
2-component sealing grouting compounds (25 l)	+	+	-
Leveling compounds (25 l)	+	+	-
2-component epoxy-resin and sand mix (30 l)	+	+	-
Heat-insulating cement (25 l)	-	+	-
High-performance mortar (Flowstone)	-	-	-
Plastic-modified mortar systems (PCC / ECC) (25l)	-	+	-
Steel fiber mortar	-	-	-

+ = suitable - = unsuitable

Information supplied without liability

Your Collomix dealer:

AOX-S (Article number 37.123)

With a high-speed mixer and separate power-driven mixing tub, for volumes of up to 40 l; two changeable mixing tools (KR/DLX) for a wide range of materials to be mixed. For small to medium-sized building sites.

Technical data

Size of mixing tub	65 liter
Max. effective volume	max. 40 litres
Power rating of mixing mechanism	1 kW
Power rating of tub drive	0,55 kW
Voltage	230 V
RPM of mixing mechanism	750
RPM of tube drive	18
Dimensions (l x w x h)	600x820x870 mm
Weight	51 kg



Mixing Tool DLX



Mixing Tool KR



POX-S (Article number 37.124)

With a permanently fixed mixing tool and rotating mixing tub it is designed for compact and plastic mortar, screed and plaster; for volumes of up to 40 l.

Technical data

Size of mixing tub	65 liter
Max. effective volume	max. 40 litres
Power rating of tub drive	0,75 kW
Voltage	230 V
RPM of tube drive	50
Dimensions (l x w x h)	600x820x770 mm
Weight	48 kg



Collomix Rühr- und Mischgeräte GmbH

Daimlerstr. 9 • 85080 Gaimersheim/Germany • Tel. ++49 (0) 8458 / 3298-0 • Fax ++49 (0)8458 / 3298-30
Email: info@collomix.de • Internet: www.collomix.de