

#### ALBAU SIA

# V 03

# Product technical data sheet

Page 1 Pages 2

# Elastic glue for waterproofing membrane





#### Technical data:

| Order No.:               | ALB-GLUE-WM/310   |  |
|--------------------------|---|--|
| Bar code:                | 4751023407302   |  |
| Composition:             | Permanently elastic glue made of specialised rubber, contains solvents. With extremely high bonding force and outstanding resistance to ageing. |  |
| Finishing:               | Above +5 °C (ambient and component temperature)   |  |
| Yield:                   | approx. 7 m/cartridge   |  |
| Contents:                | 310 ml / 310 g  |  |
| Tear strength DIN 16726: | long. approx. > 600 N / 5 cm  |  |
|                          | trans. approx. > 450 N / 5 cm   |  |
| Temperature resistance:  | -40°C to +80°C  |  |
| Shelf life:              | Within 24 months with proper storage, store in a cool place.  |  |
| Preparation time:        | 10 minutes at +5 °C   |  |

## **Description:**

Albau's elastic glue is a permanently-elastic glue for bonding and connecting waterproofing LDPE membrane, waterproofing EVA membrane and drainage membranes, and connecting these to masonry, concrete, wood, aluminium, steel, hard PVC and bitumen.

## Instruction for use:

The elastic glue adheres only to clean, dry, and grease-free substrates, which must also have a sufficient load-bearing capacity. Porous substrates must be primed. Before bonding, ensure the PE foil is suitable for use.

Proceed as follows: Apply an approx. 8 mm thick "bead" to the bonding substrate. Then press the overlapping material firmly into place. Use additional mechanical attachments such as sheet steel head nails (SKU: ALB-FIX-DM/8/50) to ensure perfect connections (for instance on masonry). Ensure good ventilation while working.

# Safety information:

Liquid and vapour are highly flammable. Causes severe eye irritation. Can cause sleepiness and dizziness. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not smoke. Take



#### **MADE IN EUROPE**



|       | ALBAU SIA                    | V 03    |
|-------|------------------------------|---------|
|       |                              | v1      |
|       | Product technical data sheet | Page 2  |
| ALBAU |                              | Pages 2 |

measures to prevent electrostatic discharge. Avoid breathing in vapour/fog/aerosol. Only use outdoors or in well ventilated rooms.

IF PRODUCT COMES INTO CONTACT WITH EYES, flush them carefully with clean water for several minutes. Remove contact lenses if possible. Continue flushing and store contact lenses in a well ventilated area. Product contains 2-butanone, ethyl acetate.