

Small countersunk head 75° with TX-Star recess, A2, partial thread



APPROVALS



ADVANTAGES/BENEFITS

- The stainless steel wood façade screw is ideally suited for safe and long-lasting connections in external areas.
- The Power-Fast thread reaches into the screw tip and ensures a fast bite. This makes your work noticeably easier.
- The shank ribs reduce drive-in resistance and thereby enable power and battery conservation in your work.
- The narrow head geometry also affords a precise and splinter-free surface finish even with fastenings close to the edge.

ADVANTAGES/BENEFITS

- The stainless steel wood façade screw is ideally suited for safe and long-lasting connections in external areas.
- The Power-Fast thread reaches into the screw tip and ensures a fast bite. This makes your work noticeably easier.
- The shank ribs reduce drive-in resistance and thereby enable power and battery conservation in your work.
- The narrow head geometry also affords a precise and splinter-free surface finish even with fastenings close to the edge.

FUNCTIONING

- The boards in the wood façades can be fastened to the substructure easily and permanently with the fischer wood façade screw with no need for pre-drilling.

TECHNICAL DATA



FFS-ST A2P

Diameter 4,5

Diameter d [mm]	Length l [mm]	Drive	Art.-No. Art.-No.	Article name	Partial thread length l _g [mm]	Sales unit [pcs]
4,5	35	TX20	660502	FFS-ST 4,5 x 35 A2P 300	24	300
4,5	40	TX20	660504	FFS-ST 4,5 x 40 A2P 300	24	300
4,5	45	TX20	660506	FFS-ST 4,5 x 45 A2P 300	30	300

Diameter	Length	Drive	Art.-No.		Partial thread length	Sales unit
d [mm]	l [mm]		Art.-No.	Article name	l _g [mm]	[pcs]
4,5	50	TX20	660508	FFS-ST 4,5 x 50 A2P 300	30	300
4,5	60	TX20	660510	FFS-ST 4,5 x 60 A2P 200	36	200
4,5	70	TX20	660512	FFS-ST 4,5 x 70 A2P 200	42	200

Diameter 5,0

Diameter d [mm]	Length l [mm]	Drive	Art.-No.	Article name	Partial thread length l _g [mm]	Sales unit [pcs]
5,0	60	TX20	660514	FFS-ST 5,0 x 60 A2P 200	36	200
5,0	70	TX20	660516	FFS-ST 5,0 x 70 A2P 100	42	100
5,0	80	TX20	660518	FFS-ST 5,0 x 80 A2P 100	50	100