

Pan head, PZ, blue zinc-plated, partial thread



APPROVALS



BUILDING MATERIALS

- Glued-laminated timber
- Cross-laminated timber
- Laminated veneer plywood panels (e.g. Multiplex)
- Hard woods (pre-drilled)
- Chipboards and oriented strand boards (e.g. OSB panels)
- Plywood
- Solid wood panels
- Soft woods
- And many other wood materials

ADVANTAGES/BENEFITS

- The unique Power-Fast thread reaches into the screw tip and ensures a fast bite. This makes your work noticeably easier with all wood materials.
- The shank ribs (for screws with partial thread from 50 mm in length and up) substantially reduce drive-in resistance and thus enable greater power and battery conservation in your work.
- The optimised head geometry enables an exact and splinter-free surface finish without the screw twisting off, even with connections close to the edge.
- The ETA approval guarantees the high safety standard and the premium quality of fischer Power-Fast screws.

APPLICATIONS

- General wood joints
- Finger tightening elements
- Safety-relevant applications
- Plankings
- Skirting
- Door and metal fittings

FUNCTIONING

- Screws with partial threads can lock wood parts into place by tightening them against each other.
- Full-thread screws are recommended for mounting thin parts and in less firm wood materials (e.g. soft woods).
- Screws with countersunk head can be flush mounted with the wood.
- Pan-Head screws are particularly well suited for metal and wood joints.
- The raised countersunk head is particularly suitable for joints where the screw head is visible and needs to leave behind an attractive appearance.

TECHNICAL DATA



FPF-PZ ZPP

Diameter 5,0

Diameter	Length	Drive	Art.-No.		ETA-approval	Partial thread length	Sales unit
d	l					l _g	
[mm]	[mm]		Art.-No.	Article name		[mm]	[pcs]
5,0	80	PZ2	652678	FPF-PZ 5,0 x 80 ZPP 100	■	50	100

Diameter 6,0

Diameter d [mm]	Length l [mm]	Drive	Art.-No.	Article name	ETA-approval	Partial thread length l _g [mm]	Sales unit [pcs]
6,0	80	PZ3	652696	FPF-PZ 6,0 x 80 ZPP 50	■	50	50
6,0	100	PZ3	652698	FPF-PZ 6,0 x 100 ZPP 50	■	60	50