


Pan head, PZ, yellow zinc-plated, full thread



APPROVALS



BUILDING MATERIALS

- Glued-laminated timber
- Cross-laminated timber
- Laminated veneer plywood panels (e.g. Multiplex)
- Hard woods (pre-drilled)
- Chipboards and oriented strand boards (e.g. OSB panels)
- Plywood
- Solid wood panels
- Soft woods
- And many other wood materials

ADVANTAGES/BENEFITS

- The unique Power-Fast thread reaches into the screw tip and ensures a fast bite. This makes your work noticeably easier with all wood materials.
- The shank ribs (for screws with partial thread from 50 mm in length and up) substantially reduce drive-in resistance and thus enable greater power and battery conservation in your work.
- The optimised head geometry enables an exact and splinter-free surface finish without the screw twisting off, even with connections close to the edge.
- The ETA approval guarantees the high safety standard and the premium quality of fischer Power-Fast screws.


APPLICATIONS

- General wood joints
- Finger tightening elements
- Safety-relevant applications
- Plankings
- Skirting
- Door and metal fittings

FUNCTIONING

- Screws with partial threads can lock wood parts into place by tightening them against each other.
- Full-thread screws are recommended for mounting thin parts and in less firm wood materials (e.g. soft woods).
- Screws with countersunk head can be flush mounted with the wood.
- Pan-Head screws are particularly well suited for metal and wood joints.
- The raised countersunk head is particularly suitable for joints where the screw head is visible and needs to leave behind an attractive appearance.

TECHNICAL DATA



FPF-PZ ZPF

Diameter 3,0

Diameter d [mm]	Length l [mm]	Drive	Art.-No.	Article name	ETA-approval	Full thread length l _g [mm]	Sales unit [pcs]
3,0	16	PZ1	652552	FPF-PZ 3,0 x 16 ZPF 200		14	200
3,0	20	PZ1	652556	FPF-PZ 3,0 x 20 ZPF 200	■	18	200
3,0	25	PZ1	652560	FPF-PZ 3,0 x 25 ZPF 200	■	23	200
3,0	30	PZ1	652564	FPF-PZ 3,0 x 30 ZPF 200	■	28	200

Diameter 3,5

Diameter d [mm]	Length l [mm]	Drive	Art.-No. Art.-No.	Article name	ETA-approval	Full thread length l _g [mm]	Sales unit [pcs]
3,5	12	PZ2	652568	FPF-PZ 3,5 x 12 ZPF 200		10	200
3,5	16	PZ2	652572	FPF-PZ 3,5 x 16 ZPF 200		14	200
3,5	20	PZ2	652576	FPF-PZ 3,5 x 20 ZPF 200	■	18	200
3,5	25	PZ2	652580	FPF-PZ 3,5 x 25 ZPF 200	■	23	200
3,5	30	PZ2	652584	FPF-PZ 3,5 x 30 ZPF 200	■	28	200
3,5	35	PZ2	652588	FPF-PZ 3,5 x 35 ZPF 200	■	33	200

Diameter 4,0

Diameter d [mm]	Length l [mm]	Drive	Art.-No. Art.-No.	Article name	ETA-approval	Full thread length l _g [mm]	Sales unit [pcs]
4,0	16	PZ2	652592	FPF-PZ 4,0 x 16 ZPF 200		13	200
4,0	20	PZ2	652596	FPF-PZ 4,0 x 20 ZPF 200		17	200
4,0	25	PZ2	652600	FPF-PZ 4,0 x 25 ZPF 200	■	22	200
4,0	30	PZ2	652604	FPF-PZ 4,0 x 30 ZPF 200	■	27	200
4,0	35	PZ2	652608	FPF-PZ 4,0 x 35 ZPF 200	■	32	200
4,0	40	PZ2	652612	FPF-PZ 4,0 x 40 ZPF 200	■	37	200
4,0	45	PZ2	652842	FPF-PZ 4,0 x 45 ZPF 200		40	200
4,0	50	PZ2	652616	FPF-PZ 4,0 x 50 ZPF 200	■	47	200
4,5	16	PZ2	652619	FPF-PZ 4,5 x 16 ZPF 200		13	200

Diameter 4,5

Diameter d [mm]	Length l [mm]	Drive	Art.-No.	Article name	ETA-approval	Full thread length l _g [mm]	Sales unit [pcs]
4,5	20	PZ2	652623	FPF-PZ 4,5 x 20 ZPF 200		17	200
4,5	25	PZ2	652627	FPF-PZ 4,5 x 25 ZPF 200	■	22	200
4,5	30	PZ2	652631	FPF-PZ 4,5 x 30 ZPF 200	■	27	200
4,5	35	PZ2	652635	FPF-PZ 4,5 x 35 ZPF 200	■	32	200
4,5	40	PZ2	652639	FPF-PZ 4,5 x 40 ZPF 200	■	37	200
4,5	45	PZ2	652843	FPF-PZ 4,5 x 45 ZPF 200		40	200
4,5	50	PZ2	652643	FPF-PZ 4,5 x 50 ZPF 200	■	47	200

Diameter 5,0

Diameter d [mm]	Length l [mm]	Drive	Art.-No.	Article name	ETA-approval	Full thread length l _g [mm]	Sales unit [pcs]
5,0	16	PZ2	652647	FPF-PZ 5,0 x 16 ZPF 200		12	200
5,0	20	PZ2	652651	FPF-PZ 5,0 x 20 ZPF 200		16	200
5,0	25	PZ2	652655	FPF-PZ 5,0 x 25 ZPF 200		21	200
5,0	30	PZ2	652659	FPF-PZ 5,0 x 30 ZPF 200	■	26	200
5,0	35	PZ2	652844	FPF-PZ 5,0 x 35 ZPF 200		30	200
5,0	40	PZ2	652663	FPF-PZ 5,0 x 40 ZPF 100	■	36	100
5,0	45	PZ2	652845	FPF-PZ 5,0 x 45 ZPF 200		30	200
5,0	50	PZ2	652667	FPF-PZ 5,0 x 50 ZPF 100	■	46	100
5,0	60	PZ2	652671	FPF-PZ 5,0 x 60 ZPF 100		56	100
5,0	70	PZ2	652675	FPF-PZ 5,0 x 70 ZPF 100		66	100

Diameter 6,0

Diameter d [mm]	Length l [mm]	Drive	Art.-No.	Article name	ETA-approval	Full thread length l _g [mm]	Sales unit [pcs]
6,0	30	PZ3	652846	FPF-PZ 6,0 x 30 ZPF 200		25	200
6,0	40	PZ3	652682	FPF-PZ 6,0 x 40 ZPF 100	■	36	100
6,0	50	PZ3	652686	FPF-PZ 6,0 x 50 ZPF 100	■	46	100
6,0	60	PZ3	652690	FPF-PZ 6,0 x 60 ZPF 100	■	56	100
6,0	70	PZ3	652693	FPF-PZ 6,0 x 70 ZPF 50	■	66	50