

# B 100

**bolle**  
SAFETY

## Light and resistant

Electric arc welding without protection is harmful.

It can cause a painful inflammation of the cornea and an irreversible opacity of the eye's crystalline lens : a cataract. Our range is entirely researched and designed to meet the requirements of standards, comfort and aesthetics.

Our team of specialists will advise you on the most suitable solution for your risks.

ref. B100F



**Europe Bollé Safety**  
95 Rue Louis Guérin  
69100 Villeurbanne - France  
tel: 00 33 (0) 4 78 85 23 64  
fax: 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

**U.K. Bollé Safety**  
Unit C83 - Barwell Business Park  
Leatherhead Road - Chessington  
Surrey - KT9 2NY  
tel. 00 44 (0)208 391 4700  
fax 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk


# B100

Passive welding range


Products ref.	DESCRIPTION	WEIGHT	STANDARDS
B100F	Mask only - fixed window 105 x 50	400 g	EN175 S 9 W CE
B100F	Mask only - fixed window 110 x 90	392 g	EN175 S 9 W CE
MP (08-14) 10550	Welding filter - mineral tint 8 to 14 - size 105 x 50	39-44 g	EN169
MP (09-14) 11090	Welding filter - mineral tint 9 to 14 - size 110 x 90	65-72 g	EN169
CR39110550	Screen guard - CR39 - size 105 x 50	10 g	N/A
CR39111090	Screen guard - CR39 - size 110 x 90	19 g	N/A
MI10550	Screen guard - clear mineral - size 105 x 50	25 g	N/A
MI11090	Screen guard - clear mineral - size 110 x 90	51 g	N/A



└ B100F



B100F  
105 x 50



B100F  
110 x 90



## CHARACTERISTICS :

Black nylon hand head shield  
Fix back view  
Fixed handle  
Conforms to EN175

**The B100F mask is supplied empty,  
that is without any filter or screen guard.**

The B100F accepts all of our standard size filters  
and screen guards.

## PACKAGING AND EAN 13 CODE :

	B100F
Individual plastic	3660740003159
N/A	N/A
20 safety spectacles per outer pack	3660740203153

Notified  
laboratories  
for  
certification :

