


## CSK head, TX, blue zinc-plated, full thread



### VERSIONS

- Zinc-plated steel, blue zinc-plated

### BUILDING MATERIALS

- Glued-laminated timber
- Cross-laminated timber
- Laminated veneer plywood panels
- Solid structural timber
- Glued timber boards on solid wood
- Soft wood (e.g. Douglas, spruce, pine, fir, etc.)
- And other wood materials

### APPROVALS



### ADVANTAGES

- The unique Power-Full thread runs from the tip to right under the head, ensuring maximum force transmission.
- The drill bit tip enables screw fitting without pre-drilling and offers guidance when screwing in. In addition, the risk of splitting is decreased and the screwing resistance is significantly reduced.
- Lower edge and axle distances are therefore possible and allowed.
- All in all, this saves on time and materials.
- The ETA approval guarantees the high safety standard and the premium quality of the fischer Power-Full screws.


### APPLICATIONS

- Safety-relevant applications
- Wood frame construction
- Post construction
- Timber houses
- Rooftop insulation systems
- Car ports
- Conservatories
- Playground equipment

### FUNCTIONALITY

- Screws with a countersunk head can be flush-mounted.
- Ideal for the fixing of metal components.

### TECHNICAL DATA



FPF-ST ZPF

Diameter 8,0

Diameter d	Length l	Drive	Art.-No.		ETA-approval	Full thread length l <sub>g</sub>	Sales unit
[mm]	[mm]		Art.-No.	Article name		[mm]	[pcs]
8,0	95	TX40	<b>659385</b>	<b>FPF-ST 8,0 x 95 ZPF 50</b>		80	50
8,0	125	TX40	<b>659386</b>	<b>FPF-ST 8,0 x 125 ZPF 50</b>		110	50
8,0	155	TX40	<b>659387</b>	<b>FPF-ST 8,0 x 155 ZPF 50</b>		140	50
8,0	195	TX40	<b>659388</b>	<b>FPF-ST 8,0 x 195 ZPF 50</b>		180	50
8,0	220	TX40	<b>659389</b>	<b>FPF-ST 8,0 x 220 ZPF 50</b>		205	50
8,0	245	TX40	<b>659390</b>	<b>FPF-ST 8,0 x 245 ZPF 50</b>		230	50
8,0	270	TX40	<b>659418</b>	<b>FPF-ST 8,0 x 270 ZPF 50</b>		255	50
8,0	295	TX40	<b>659419</b>	<b>FPF-ST 8,0 x 295 ZPF 50</b>		280	50
8,0	330	TX40	<b>659420</b>	<b>FPF-ST 8,0 x 330 ZPF 50</b>		315	50
8,0	375	TX40	<b>659421</b>	<b>FPF-ST 8,0 x 375 ZPF 50</b>		360	50
8,0	400	TX40	<b>659422</b>	<b>FPF-ST 8,0 x 400 ZPF 50</b>		385	50

## Diameter 10,0

Diameter d	Length l	Drive	Art.-No.		ETA-approval	Full thread length l <sub>g</sub>	Sales unit
[mm]	[mm]		Art.-No.	Article name		[mm]	[pcs]
10,0	125	TX50	<b>659423</b>	<b>FPF-ST 10,0 x 125 ZPF 50</b>		110	50
10,0	155	TX50	<b>659424</b>	<b>FPF-ST 10,0 x 155 ZPF 50</b>		140	50
10,0	195	TX50	<b>659425</b>	<b>FPF-ST 10,0 x 195 ZPF 50</b>		180	50
10,0	220	TX50	<b>659426</b>	<b>FPF-ST 10,0 x 220 ZPF 50</b>		205	50
10,0	245	TX50	<b>659427</b>	<b>FPF-ST 10,0 x 245 ZPF 50</b>		230	50
10,0	270	TX50	<b>659428</b>	<b>FPF-ST 10,0 x 270 ZPF 50</b>		255	50
10,0	300	TX50	<b>659429</b>	<b>FPF-ST 10,0 x 300 ZPF 50</b>		285	50