Commercial Product Name: FIS SB 390/585/1500 S Mortar (Component



A)

Revision Date: 29.03.2017 Replaces version from: 22.03.2017 Version: 2.4 /en

Print date: 05.04.2017

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Commercial Product Name FIS SB 390/585/1500 S Mortar (Component A)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses composite mortar

Recommended restrictions None under normal processing. Observe technical data sheet.

1.3 Details of the supplier of the safety data sheet

Company designation fischerwerke GmbH & Co. KG

> Klaus-Fischer-Straße 1 D-72178 Waldachtal

Telephone: +49(0)7443 12-0 FAX: +49(0)7443 12-4222 Email: info-sdb@fischer.de Internet: www.fischer.de

Marketer Great Britain: Mrs Mirka Valovicova, fischer Fixing (UK) Ltd, Hithercroft

Road, Wallingford, Oxfordshire, OX10 9AT, Tel. 01491 827 920, Fax

01491 827 950

1.4 Emergency telephone number

Emergency telephone number +49(0)6132-84463 (24h)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Reg-Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT SE 3;

ulation (EC) No. 1272/2008 H335

2.2 Label elements

Hazard pictogram



GHS05



Signal word Danger

Hazardous component(s) to be


indicated on label

Cement, portland, chemicals, 2-hydroxypropyl methacrylate

H-statement(s) H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.





A)

Revision Date: 29.03.2017 Replaces version from: 22.03.2017

Version: 2.4 /en Print date: 05.04.2017

H335: May cause respiratory irritation.

P-statement(s) P101: If medical advice is needed, have product container or label at

hand.

P102: Keep out of reach of children.

P280: Wear protective gloves/protective clothing/eye protection/face

protection.

None known.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

P310: Immediately call a POISON CENTER or doctor/physician.

2.3 Other hazards

Health hazard None known.

Particular information pertain-

ing specific risk for human / en-

vironment

Indication of danger None known.
Hazard precautions None known.

SECTION 3: Composition/information on ingredients

Hazardous ingredients

Ingredient		Classification (EC) 1272/2008	Concen- tration
Cement, portland, chemi- cals	CAS No.: 65997-15-1 EC-No.: 266-043-4 REACH No.: The sub- stance does not require registration according to Regulation (EC) No 1207/2006 [REACH].	Skin Irrit. 2;H315 Eye Dam. 1; H318 STOT SE 3;H335	25.0 – 50.0 % by weight
2-hydroxypropyl methacry- late	CAS No. : 27813-02-1 EC-No. : 248-666-3 REACH No. : 01-2119490226-37	Skin Sens. 1; H317 Eye Irrit. 2; H319	2.5 – 10.0 % by weight

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice If symptoms persist, call a physician.

Remove/Take off immediately all contaminated clothing.

If inhaled IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

In case of skin contact IF ON SKIN: Gently wash with plenty of soap and water.

In case of eye contact In case of eye contact, remove contact lens and rinse immediately

with plenty of water, also under the eyelids, for at least 15 minutes.

Commercial Product Name: FIS SB 390/585/1500 S Mortar (Component



A)

Revision Date: 29.03.2017 Replaces version from: 22.03.2017

Print date: 05.04.2017 Version: 2.4 /en

If swallowed If swallowed, seek medical advice immediately and show this contain-

er or label.

Clean mouth with water and drink afterwards plenty of water. Drink 1

or 2 glasses of water. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

None known. **Symptoms**

4.3 Indication of any immediate medical attention and special treatment needed

Immediate medical attention No data available Special medical treatment No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2)

Dry powder

Foam

Water spray jet

Extinguishing media which must High volume water jet

not be used for safety reasons

5.2 Special hazards arising from the substance or mixture

Special exposure hazards arising Heating or fire can release toxic gas.

from the substance or preparation itself, its combustion prod-

ucts, or released gases

5.3 Advice for firefighters

Special protective equipment for In the event of fire, wear self-contained breathing apparatus. firefighting

In the event of fire and/or explosion do not breathe fumes.

Additional information on fire-

fighting

Fire residues and contaminated fire extinguishing water must be dis-

posed of in accordance with local regulations.

Keep containers and surroundings cool with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Environmental precautions The product should not be allowed to enter drains, water courses or

the soil.

Commercial Product Name: FIS SB 390/585/1500 S Mortar (Component



A)

Revision Date: 29.03.2017 Replaces version from: 22.03.2017

Print date: 05.04.2017 Version: 2.4 /en

Prevent spreading over a wide area (e.g. by containment or oil barri-

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Use mechanical handling equipment.

Treat recovered material as described in the section "Disposal consid-

erations".

6.4 Reference to other sections

Reference to other sections See chapter 8/13

6.5 Additional information

Other information Dispose of in accordance with local regulations.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling None under normal processing.

Caution: During machining in cured state dust is formed.

and explosion

Advice on protection against fire No special precautions required.

7.2 Conditions for safe storage, including any incompatibilities

Storage space and container re-

Keep containers tightly closed in a cool, well-ventilated place.

auirements

Store in accordance with local regulations.

Keep only in original container.

Hints on storage assembly Store in accordance with the particular national regulations.

10-13 (TRGS 510) German storage class

7.3 Specific end use(s)

Specific use(s) composite mortar

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Cement, portland, chemicals

Great Britain

Long-term exposure value/ mg/m3	Remarks	Source
10	inhalable dust	100
4	respirable dust	100

Source: 100 - Company data

Commercial Product Name: FIS SB 390/585/1500 S Mortar (Component



A)

Revision Date: 29.03.2017 Replaces version from: 22.03.2017

Version : 2.4 /en Print date : 05.04.2017

8.2 Exposure controls

Respiratory protection No personal respiratory protective equipment normally required.

Hand protection not required under normal use

Suitable material: butyl-rubber, Chloroprene, Nitrile rubber

Unsuitable material: PVC disposable gloves

Material thickness: adjust to application and duration of use

Break through time: adjust to application and duration of use

Remarks: Take note of the information given by the producer concerning per-

meability and break through times, and of special workplace condi-

tions (mechanical strain, duration of contact).

Reference substance : Replace when worn.

Eye protection Tightly fitting safety goggles

Skin and body protection Wear suitable protective equipment.

Note: Choose body protection according to the amount and concentration

of the dangerous substance at the work place.

General protective and hygiene

measures

Smoking, eating and drinking should be prohibited in the application

area.

Avoid contact with skin, eyes and clothing.

Take off all contaminated clothing immediately.

Wash hands before breaks and at the end of workday.

Keep away from food, drink and animal feedingstuffs.

Use protective skin cream before handling the product.

Information on environmental

protection regulations

No special environmental precautions required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form paste

Colour light grey

Odour characteristic

Odour threshold not determined

pH No data available

Melting point [°C] / Freezing

point [°C]

No data available

Boiling point [°C] no data available

Flash point [°C] > 100

Commercial Product Name: FIS SB 390/585/1500 S Mortar (Component



A)

Revision Date: 29.03.2017 Replaces version from: 22.03.2017

Print date: 05.04.2017

Evaporation rate [kg/(s*m²)] No data available

Flammability (solid, gas) No data available

Explosion limits [Vol-%]

Version: 2.4 /en

Lower limit : not determined

Upper limit : not determined

Vapour pressure [kPa] No data available
Vapour density No data available

Density $[g/cm^3]$ 1,7 - 1,8

Temperature: 20 °C

Relative density

Solubility

No data available

Water solubility [g/l]

No data available

No data available

No data available

Partition coefficient n-octanol /

water (log P O/W)

No data available

Autoinflammability not auto-flammable

Decomposition temperature [°C] not determined

Viscosity, dynamic [kg/(m*s)] 120 - 160

Temperature: 20 °C

Explosive properties Not explosive Risk of explosion. Not explosive

Oxidising properties No

9.2 Other information

Relative vapour density (air=1) not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

Thermal decomposition No decomposition if stored and applied as directed.

10.2 Chemical stability

Chemical stability Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions No dangerous reaction known under conditions of normal use.

Commercial Product Name: FIS SB 390/585/1500 S Mortar (Component



A)

Revision Date: 29.03.2017 Replaces version from: 22.03.2017

10.4 Conditions to avoid

Conditions to avoid No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid Not applicable.

10.6 Hazardous decomposition products

Hazardous decomposition prod- No decomposition if used as directed.

ucts

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Hazardous ingredients

Cement, portland, chemicals

Oral toxicity [mg/kg]	Test criterion	Remarks	Source
> 2000	LD50	literature value	100

Source: 100 - Company data

Dermal toxicity [mg/kg]	Test criterion	Test species	Remarks	Source
> 2000	LD50	rabbit	Limit test 2000 mg/kg	100

Source: 100 - Company data

Inhalative toxicity	Test criterion	Test species	Note	Source
[mg/l]				
> 5	LC50	rat	Limit Test 5 g/m³	100

Source: 100 - Company data

Sensitization May cause an allergic skin reaction.

Carcinogenic effects Not applicable.

Mutagenicity Not applicable.

Reproduction toxicity Not applicable.

Caustic effect No data available

Specific target organ toxicity (single expo-	Specific effects	Source
sure) [mg/kg]		
	Irritating to respiratory system. (dust)	100

Source: 100 - Company data

Specific target organ toxicity (repeated expo-	Remarks	Source
sure) [mg/kg]		
	Not applicable.	100

Source: 100 - Company data

Commercial Product Name: FIS SB 390/585/1500 S Mortar (Component



A)

Revision Date: 29.03.2017 Replaces version from: 22.03.2017

2-hydroxypropyl methacrylate

Oral toxicity [mg/kg]	Test criterion	Test species	Remarks	Source
> 2000	LD50	rat	OECD 401 Limit Test.	100

Source: 100 - Company data

Dermal toxicity [mg/kg]	Test criterion	Test species	Source
> 5000	LD50	rabbit	100

Source: 100 - Company data

Inhalative toxicity [mg/l]	Source
No data available	100

Source: 100 - Company data

Sensitization Skin sensitizer
Carcinogenic effects Not applicable.
Mutagenicity Not applicable.

Remarks OECD 471 (Ames Test) / OECD 476.

Reproduction toxicity Not applicable.

Remarks OECD 422.

Caustic effect Not applicable.

Specific target organ toxicity (single exposure) [mg/kg]	Remarks	Source
	Not applicable.	100

Source: 100 - Company data

Specific target organ toxicity (repeated expo-	Remarks	Source
sure) [mg/kg]		
	Not applicable.	100

Source: 100 - Company data

11.2 Additional information

Other information (chapter 11.) The product itself has not been tested.

SECTION 12: Ecological information

12.1 Toxicity

Hazardous ingredients

Cement, portland, chemicals

Toxicity to fish [mg/l]	Test criterion	Source
> 100	LC50	100

Commercial Product Name: FIS SB 390/585/1500 S Mortar (Component



A)

Revision Date: 29.03.2017 Replaces version from: 22.03.2017 Version: 2.4 /en

Print date: 05.04.2017

Source: 100 - Company data

Toxicity to daphnia [mg/l]	Test criterion	Test species	Source
> 100	LC50	Daphnia magna (Water flea)	100

Source: 100 - Company data

Toxicity to algae [mg/l]	Test criterion	Source
> 100	EC50	100

Source: 100 - Company data

Not applicable. (inorganic) Biodegradability

2-hydroxypropyl methacrylate

Toxicity to fish [mg/l]	Test criterion	Test species	Measuring method	Exposure dura- tion	Source
493	LC50	Leuciscus idus (Golden orfe)	DIN 38412	48 h	100

Source: 100 - Company data

Toxicity to daph- nia [mg/l]	Test criterion	Test species	Exposure dura- tion	Measuring method	Source
> 130	EC50	Daphnia magna (Water flea)	48 h	OECD Test Guide- line 202	100

Source: 100 - Company data

Toxicity to algae	Test criterion	Test species	Exposure dura-	Measuring	Source
[mg/l]			tion	method	
> 97,2	EC50	Selenastrum capri-	72 h	OECD Test Guide-	100
		cornutum		line 201	

Source: 100 - Company data

NOEC (daphnia)	Test criterion	Test species	Measuring	Exposure dura-	Source
[mg/l]			method	tion	
24,1	NOEC	Daphnia magna	OECD 202	21 d	100
		(Big water flea).			

Source: 100 - Company data

Biodegradability Readily biodegradable.

Ready degradability

12.2 Persistence and degradability

Elimination and distribution There is no data available for this product.

mechanisms

Elimination in purification plant There is no data available for this product.

12.3 Bioaccumulative potential

Bioaccumulation There is no data available for this product. Bioconcentration factor (BCF) There is no data available for this product.

Commercial Product Name: FIS SB 390/585/1500 S Mortar (Component



A)

Revision Date: 29.03.2017 Replaces version from: 22.03.2017

Version: 2.4 /en Print date: 05.04.2017

12.4 Mobility in soil

Distribution in the environment
There is no data available for this product.

Mobility

Mobility: There is no data available for this product.

12.5 Results of PBT and vPvB assessment

Results of PBT characteristics

determination

This preparation contains no substance considered to be very persis-

tent nor very bioaccumulating (vPvB).

12.6 Other adverse effects

Further information on ecology The product itself has not been tested.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal considerations The product should not be allowed to enter drains, water courses or

the soil.

Dispose of waste according to applicable legislation.

Empty remaining contents.

Waste Code According to the European Waste Catalogue, Waste Codes are not

product specific, but application specific.

The following Waste Codes are only suggestions:

Product (Mortar and Curing agent)

200127 - paint, inks, adhesives and resins containing dangerous

substances

080409 - waste adhesives and sealants containing organic solvents

or other dangerous substances

cured material and completely squeezed cartridges

200000 - MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING

SEPARATELY COLLECTED FRACTIONS

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG	Air transport ICAO/IATA
14.1 UN-No	Not applicable.	Not applicable.	Not applicable.
14.2 Description of the	No dangerous good ac-	No dangerous good ac-	No dangerous good ac-
goods	cording to ADR	cording to IMDG	cording to IATA
14.2 UN proper shipping		Non dangerous good	Non dangerous good
name			
14.3 Transport hazard	Not applicable.	Not applicable.	Not applicable.
class(es)			
14.4 Packaging group	Not applicable.	Not applicable.	Not applicable.
14.5 Environmental haz-	Not applicable.	Not applicable.	Not applicable.
ards			
Danger releasing sub-	Not applicable.	Not applicable.	Not applicable.
stance			

Commercial Product Name: FIS SB 390/585/1500 S Mortar (Component



A)

Revision Date: 29.03.2017 Replaces version from: 22.03.2017

Print date: 05.04.2017 Version: 2.4 /en

14.6 Special precautions for user

Precautions not required under normal use

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to

not applicable

Annex II of MARPOL and the IBC

Code

14.8 Additional information

Other information (chapter 14.) Not dangerous goods in the meaning of ADR/RID, ADNR, IMDG-Code,

ICAO/IATA-DGR

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Decopaint regulation Exempt

Carcinogenic hazardous subno

stance as per Annex II GefStoffV

Restriction of occupation. Exempt

Water Hazard Class (Ger.) 1

Cassification in compliance with

the Industrial Safety Regulation

Exempt

15.2 Chemical safety assessment

Not relevant. Chemical safety assessments for substances in this mix-Safety assessment

ture were not carried out.

Additional regulations Not applicable.

SECTION 16: Other information

Relevant H-phrases H315: Causes skin irritation.

H317: May cause an allergic skin reaction.


H318: Causes serious eye damage. H319: Causes serious eye irritation. H335: May cause respiratory irritation.

Wording of the hazard classes Skin Irrit.: Skin irritation

> Eye Dam.: Serious eye damage Skin Sens.: Skin sensitization

STOT SE: Specific target organ toxicity - single exposure

Eye Irrit.: Serious eye irritation





A)

Revision Date: 29.03.2017 Replaces version from: 22.03.2017 Version: 2.4 /en

Print date: 05.04.2017

Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]

Classification	Evaluation
Skin Irrit. 2; H315	Calculated
Eye Dam. 1; H318	Calculated
Skin Sens. 1; H317	Calculated
STOT SE 3; H335	Calculated

Recommended restrictions

None under normal processing. Observe technical data sheet.

Modifications of the previous version are denoted with an asterisk (*).

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.

Commercial Product Name: FIS SB 390/585/1500 S Hardener (Compo-

nent B)

Revision Date: 29.03.2017 Replaces version from: 22.03.2017 Version: 4.4 /en

Print date: 05.04.2017

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Commercial Product Name FIS SB 390/585/1500 S Hardener (Component B)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses composite mortar

Recommended restrictions None under normal processing. Observe technical data sheet.

1.3 Details of the supplier of the safety data sheet

Company designation fischerwerke GmbH & Co. KG

> Klaus-Fischer-Straße 1 D-72178 Waldachtal

Telephone: +49(0)7443 12-0 FAX: +49(0)7443 12-4222 Email: info-sdb@fischer.de Internet: www.fischer.de

Marketer Great Britain: Mrs Mirka Valovicova, fischer Fixing (UK) Ltd, Hithercroft

Road, Wallingford, Oxfordshire, OX10 9AT, Tel. 01491 827 920, Fax

01491 827 950

1.4 Emergency telephone number

Emergency telephone number +49(0)6132-84463 (24h)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Reg-Skin Sens. 1; H317 Aquatic Chronic 2; H411

ulation (EC) No. 1272/2008

2.2 Label elements

Hazard pictogram



GHS07



GHS09

Signal word Warning

Hazardous component(s) to be

indicated on label

dibenzoyl peroxide

H-statement(s) H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

Commercial Product Name: FIS SB 390/585/1500 S Hardener (Compo-

nent B)

Revision Date: 29.03.2017 Replaces version from: 22.03.2017

Version : 4.4 /en Print date : 05.04.2017

P-statement(s) P101: If medical advice is needed, have product container or label at

hand.

P102: Keep out of reach of children.

P280: Wear protective gloves/protective clothing/eye protection/face

protection.

2.3 Other hazards

Health hazard None known.

Particular information pertain-

ing specific risk for human / en-

vironment

None known.

Indication of danger None known.
Hazard precautions None known.

SECTION 3: Composition/information on ingredients

Hazardous ingredients

Ingredient		Classification (EC) 1272/2008	Concen- tration
ethanediol, ethylene glycol	CAS No.: 107-21-1 EC-No.: 203-473-3 Index-No.: 603-027-00-1 REACH No.: 01-2119456816-28	Acute Tox. 4; H302 STOT RE 2; H373	< 10.0 % by weight
dibenzoyl peroxide	CAS No.: 94-36-0 EC-No.: 202-327-6 Index-No.: 617-008-00-0 REACH No.: 01-2119511472-50	Org. Perox. B; H241 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Acute 1; H400	2.5 – 10.0 % by weight

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice If symptoms persist, call a physician.

Remove/Take off immediately all contaminated clothing.

If inhaled IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

In case of skin contact IF ON SKIN: Gently wash with plenty of soap and water.

with plenty of water, also under the eyelids, for at least 15 minutes.

If swallowed, seek medical advice immediately and show this contain-

er or label.

Clean mouth with water and drink afterwards plenty of water. Drink 1

or 2 glasses of water.

Do NOT induce vomiting.

Commercial Product Name: FIS SB 390/585/1500 S Hardener (Compo-

nent B)

Revision Date: 29.03.2017 Replaces version from: 22.03.2017 Version: 4.4 /en

Print date: 05.04.2017

4.2 Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3 Indication of any immediate medical attention and special treatment needed

Immediate medical attention No data available Special medical treatment No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2)

Dry powder

Foam

Water spray jet

Extinguishing media which must High volume water jet

not be used for safety reasons

5.2 Special hazards arising from the substance or mixture

Special exposure hazards arising Heating or fire can release toxic gas.

from the substance or preparation itself, its combustion prod-

ucts, or released gases

5.3 Advice for firefighters

Special protective equipment for In the event of fire, wear self-contained breathing apparatus. firefighting

In the event of fire and/or explosion do not breathe fumes.

Additional information on fire-

fighting

Fire residues and contaminated fire extinguishing water must be dis-

posed of in accordance with local regulations.

Keep containers and surroundings cool with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Environmental precautions The product should not be allowed to enter drains, water courses or

the soil.

Prevent spreading over a wide area (e.g. by containment or oil barri-

ers).

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Use mechanical handling equipment.

Commercial Product Name: FIS SB 390/585/1500 S Hardener (Compo-



Revision Date: 29.03.2017 Replaces version from: 22.03.2017

Print date: 05.04.2017 Version: 4.4 /en

Treat recovered material as described in the section "Disposal consid-

erations".

6.4 Reference to other sections

Reference to other sections See chapter 8/13

6.5 Additional information

Other information Dispose of in accordance with local regulations.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling None under normal processing.

Caution: During machining in cured state dust is formed.

and explosion

Advice on protection against fire No special precautions required.

7.2 Conditions for safe storage, including any incompatibilities

Storage space and container re-

quirements

Keep containers tightly closed in a cool, well-ventilated place.

Store in accordance with local regulations.

Keep only in original container.

Hints on storage assembly Store in accordance with the particular national regulations.

German storage class 10-13 (TRGS 510)

7.3 Specific end use(s)

Specific use(s) composite mortar

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

ethanediol, ethylene glycol

Great Britain

Long-term expo- sure value/ ppm		Short-term ex- posure value / ppm	Short-term ex- posure value / mg/m3	Remarks	Source
	10			particulate; Can be absorbed through the skin.	19
20	52	40	104	vapour; Can be absorbed through the skin.	19

Source: 19 - EH40/2005 Workplace exposure limits (2011)

Commercial Product Name: FIS SB 390/585/1500 S Hardener (Compo-



Revision Date: 29.03.2017 Replaces version from: 22.03.2017

Version : 4.4 /en Print date : 05.04.2017

Europe

Long-term	Long-term	Short-term	Short-term	Note	Issuing date	Source
exposure val-	exposure val-	exposure val-	exposure val-			
ue/ mg/m3	ue/ ppm	ue / mg/m3	ue / ppm			
52	20	104	40	Skin	2000/39	24

Source: 24 - DIRECTIVE 2009/161/EU

dibenzoyl peroxide

Great Britain

Long-term exposure value/ mg/m3	Remarks	Source
5	R2, 36, 43	100

Source: 100 - Company data

8.2 Exposure controls

Respiratory protection No personal respiratory protective equipment normally required.

Hand protection not required under normal use

Suitable material: butyl-rubber, Chloroprene, Nitrile rubber

Unsuitable material : PVC disposable gloves

Material thickness: adjust to application and duration of use

Break through time: adjust to application and duration of use

Remarks: Take note of the information given by the producer concerning per-

meability and break through times, and of special workplace condi-

tions (mechanical strain, duration of contact).

Reference substance : Replace when worn.

Eye protection Tightly fitting safety goggles

Skin and body protection Wear suitable protective equipment.

Note: Choose body protection according to the amount and concentration

of the dangerous substance at the work place.

General protective and hygiene

measures

Smoking, eating and drinking should be prohibited in the application

area.

Avoid contact with skin, eyes and clothing.

Take off all contaminated clothing immediately.

Wash hands before breaks and at the end of workday.

Keep away from food, drink and animal feedingstuffs.

Use protective skin cream before handling the product.

Information on environmental

protection regulations

No special environmental precautions required.

Commercial Product Name: FIS SB 390/585/1500 S Hardener (Compo-

nent B)

Version: 4.4 /en

Revision Date: 29.03.2017 Replaces version from: 22.03.2017

Print date: 05.04.2017

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form paste

Colour black

Odour characteristic

Odour threshold not determined

pH No data available

Melting point [°C] / Freezing

point [°C]

No data available

Boiling point [°C] no data available

Flash point [°C] > 100

Evaporation rate [kg/(s*m²)] No data available

Flammability (solid, gas) No data available

Explosion limits [Vol-%]

Lower limit : not determined

Upper limit : not determined

Vapour pressure [kPa] No data available

Density $[g/cm^3]$ 1,7 - 1,9

Temperature: 20 °C

Water solubility [g/l] not determined

Solubility [g/l] No data available

Partition coefficient n-octanol /

water (log P O/W)

No data available

Autoinflammability not auto-flammable

Decomposition temperature [°C] not determined

Viscosity, dynamic [kg/(m*s)] 70 - 110

Temperature: 20 °C

Risk of explosion. Not explosive

9.2 Other information

Relative vapour density (air=1) not determined

Commercial Product Name: FIS SB 390/585/1500 S Hardener (Compo-



Revision Date: 29.03.2017 Replaces version from: 22.03.2017

Version: 4.4 /en Print date: 05.04.2017

SECTION 10: Stability and reactivity

10.1 Reactivity

Thermal decomposition No decomposition if stored and applied as directed.

10.2 Chemical stability

Chemical stability Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid Not applicable.

10.6 Hazardous decomposition products

Hazardous decomposition prod- No decomposition if used as directed.

ucts

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Hazardous ingredients

ethanediol, ethylene glycol

Oral toxicity [mg/kg]	Source
Harmful if swallowed.	100

Source: 100 - Company data

Dermal toxicity [mg/kg]	Test criterion	Test species	Source
> 3500	LD50	rabbit	100

Source: 100 - Company data

Inhalative toxicity	Test criterion	Test species	Note	Exposure dura-	Source
[mg/l]				tion	
> 2,5	LC50	rat	(as aerosol)	6 h	100

Source: 100 - Company data

Sensitization not sensitising.

Carcinogenic effects Contains no ingredient listed as a carcinogen

Mutagenicity Not applicable.

Reproduction toxicity Not applicable.

Caustic effect No data available

Commercial Product Name: FIS SB 390/585/1500 S Hardener (Compo-



Revision Date: 29.03.2017 Replaces version from: 22.03.2017

Version : 4.4 /en Print date : 05.04.2017

Specific target organ toxicity (repeated ex- posure) [mg/kg]	Route of exposure	Organs affected	Specific effects	Source
	Ingestion	Causes damage to kid- neys if swallowed.	Causes damage to or- gans through pro- longed or repeated ex- posure.	100
	Skin contact	May cause damage to kidneys in contact with skin.	Causes damage to or- gans through pro- longed or repeated ex- posure.	100

Source: 100 - Company data

dibenzoyl peroxide

Oral toxicity [mg/kg]	Test criterion	Test species	Source
> 5000	LD50	rat	100

Source: 100 - Company data

Inhalative toxicity [mg/l]	Test criterion	Test species	Note	Source
24300	LC50	rat	(dust)	100

Source: 100 - Company data

11.2 Additional information

Other information (chapter 11.) The product itself has not been tested.

SECTION 12: Ecological information

12.1 Toxicity

Hazardous ingredients

ethanediol, ethylene glycol

Toxicity to fish [mg/l]	Test criterion	Test species	Exposure duration	Source
72860	LC50	Pimephales promelas	96 h	100
		(Pimephales promelas		
		(fathead minnow))		

Source: 100 - Company data

Toxicity to daphnia [mg/l]	Test criterion	Test species	Exposure duration	Source
> 100	EC50	Daphnia magna (Water flea)	48 h	100

Source: 100 - Company data

Commercial Product Name: FIS SB 390/585/1500 S Hardener (Compo-

nent B)

Revision Date: 29.03.2017 Replaces version from: 22.03.2017 Version: 4.4 /en

Print date: 05.04.2017

Toxicity to algae [mg/	Test criterion	Test species	Exposure duration	Source
> 6500	EC50	Selenastrum capricor- nutum	96 h	100

Source: 100 - Company data

NOEC (fish) [mg/l]	Test criterion	Test species	Exposure duration	Source
15380	NOEC	Pimephales promelas	7 d	100
		(fathead minnow)		

Source: 100 - Company data

Biodegradability 90 - 100 %

Ready degradability

dibenzoyl peroxide

Toxicity to fish [mg/l]	Test criterion	Exposure duration	Source
0,06	LC50	96 h	100

Source: 100 - Company data

Toxicity to daphnia [mg/l]	Test criterion	Test species	Exposure duration	Source
0,11	EC50	Daphnia magna (Water flea)	48 h	100

Source: 100 - Company data

Toxicity to algae [mg/l]	Test criterion	Exposure duration	Source
0,06	EC50	72 h	100

Source: 100 - Company data

Ready degradability

NOEC (daphnia) [mg/l]

Value	Test species	Measuring method	Exposure duration
1	Daphnia magna (Big water	OECD 202	48 h
	flea).		

NOEC (algae) [mg/l]

Value	Test species	Measuring method	Exposure duration
0,5	Pseudokirchneriella sub-	OECD 201	72 h
	capitata		

12.2 Persistence and degradability

Elimination and distribution There is no data available for this product.

mechanisms

Elimination in purification plant There is no data available for this product.

12.3 Bioaccumulative potential

Bioaccumulation There is no data available for this product.

Commercial Product Name: FIS SB 390/585/1500 S Hardener (Compo-

nent B)

Revision Date: 29.03.2017 Replaces version from: 22.03.2017 Version: 4.4 /en

Print date: 05.04.2017

There is no data available for this product. Bioconcentration factor (BCF)

12.4 Mobility in soil

Distribution in the environment There is no data available for this product.

Mobility

Mobility: There is no data available for this product.

12.5 Results of PBT and vPvB assessment

Results of PBT characteristics

determination

This preparation contains no substance considered to be very persis-

tent nor very bioaccumulating (vPvB).

12.6 Other adverse effects

Further information on ecology The product should not be allowed to enter drains, water courses or

the soil.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal considerations The product should not be allowed to enter drains, water courses or

Dispose of waste according to applicable legislation.

Empty remaining contents.

Waste Code According to the European Waste Catalogue, Waste Codes are not

product specific, but application specific.

The following Waste Codes are only suggestions:

Product (Mortar and Curing agent)

200127 - paint, inks, adhesives and resins containing dangerous

substances

080409 - waste adhesives and sealants containing organic solvents

or other dangerous substances

cured material and completely squeezed cartridges

200000 - MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING

SEPARATELY COLLECTED FRACTIONS

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG	Air transport ICAO/IATA
14.1 UN-No	3077	3077	3077
14.2 Description of the	ENVIRONMENTALLY HAZ-	ENVIRONMENTALLY HAZ-	ENVIRONMENTALLY HAZ-
goods	ARDOUS SUBSTANCE,	ARDOUS SUBSTANCE,	ARDOUS SUBSTANCE,
	SOLID, N.O.S. (dibenzoyl	SOLID, N.O.S. (dibenzoyl	SOLID, N.O.S. (dibenzoyl
	peroxide)	peroxide)	peroxide)
14.2 UN proper shipping		ENVIRONMENTALLY HAZ-	Environmentally haz-
name		ARDOUS SUBSTANCE,	ardous substance, solid,
		SOLID, N.O.S. (dibenzoyl	n.o.s. (dibenzoyl peroxide)
		peroxide)	

Commercial Product Name: FIS SB 390/585/1500 S Hardener (Compo-



Revision Date: 29.03.2017 Replaces version from: 22.03.2017

Version: 4.4 /en Print date: 05.04.2017

	Land transport ADR/RID	Marine transport IMDG	Air transport ICAO/IATA
14.3 Transport hazard	9	9	9
class(es)			
14.4 Packaging group	III	III	III
14.5 Environmental haz-	U – Environmentally haz-	U – marine pollutant	U – Environmentally haz-
ards	ardous		ardous
Remarks	Not dangerous goods in	Not dangerous goods in	Not dangerous goods in
	original packaging (Special	original packaging (Special	original packaging (Special
	Provision 375)	Provision 969)	Provision A197)

14.6 Special precautions for user

Precautions not required under normal use

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to not applicable

Annex II of MARPOL and the IBC

Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Restriction of occupation. –
Water Hazard Class (Ger.) 1

15.2 Chemical safety assessment

Safety assessment Not relevant. Chemical safety assessments for substances in this mix-

ture were not carried out.

Additional regulations Not applicable.

SECTION 16: Other information

Relevant H-phrases H241: Heating may cause a fire or explosion.

H302: Harmful if swallowed.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H373: May cause damage to organs through prolonged or repeated

exposure.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

Wording of the hazard classes Skin Sens.: Skin sensitization

Aquatic Chronic: Hazardous to the aquatic environment

Acute Tox.: Acute toxicity

STOT RE: Specific target organ toxicity - repeated exposure

Org. Perox.: Organic peroxide Eye Irrit.: Serious eye irritation

Commercial Product Name: FIS SB 390/585/1500 S Hardener (Compo-



Revision Date: 29.03.2017 Replaces version from: 22.03.2017 Version: 4.4 /en

Print date: 05.04.2017

Aquatic Acute: Hazardous to the aquatic environment

Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]

Classification	Evaluation
Skin Sens. 1; H317	Calculated
Aquatic Chronic 2; H411	Data obtained by expert judgement.

Recommended restrictions None under normal processing. Observe technical data sheet.

Modifications of the previous version are denoted with an asterisk (*).

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.