Collomix



Forced-action mixers XM 3 - 900

When peak performance is required, professionals choose the XM



- Mixing material: Reaction resin compounds, exterior insulation finishing systems, concrete (-16 mm) floor coatings, all types of mortar, screed, fillers, etc.
- Tub edge scraper with a rubber lip
- 2 tool options with different speeds
- Timer (90, 180 sec./continuous)
- Short mixing times for high hourly throughputs of material
- Items supplied: 3-piece set of mixing tools
 + 1 x 90 liter special mortar tub
- Trolley recommended (extra)

Technical data XM 2 - 650			
Size of mixing tub	90 Ltr.		
Max. effective volume	max. 70 litres		
RPM of mixing mechanism	2x120/1x630		
Edge scraper speed	40 min ⁻¹		
Power supply	400 V		
Dimensions (lxwxh)	107,5x73x84,5 cm		
Weight:	117 kg		

mixing material and keconinended	Volumes	(max. 70 L)
Material (weight without addition of water):		
	Werkzeugsatz 1	Werkzeugsatz 2
	(n)	

			\ \ H-2
Consistency range: Very stiff to p	olastic		
Slightly moist concrete with grain size of -8	mm	+	-
Concrete with a max. grain size of 8		+	-
Cement screed		+	-
Synthetic resin screed		+	-
Cement Mortar		+	-
Gypsum-lime mortar		+	-
Light wall mortar		+	-
Cement stucco		+	-
Gypsum plaster		+	-
Loam plaster without fibers		+	-
Heat-insulating plaster		+	-
Air-entrained light exterior plaster		+	-
Mortar for natural stone slabs		+	-
2-component slab pointing mortar (-1,2 mm	ו)	+	-
Middle-bed mortar		+	-
Tile adhesive (flex mortar)		+	-
Pointing mortar		+	-
Consistency range: soft to sprea	ding		
Soft/spreading types of screed		+	+
Soft/spreading types of mortar		+	
Thin-bed mortar, cement for concrete precis	ion blocks	-	+
Creamy types of plaster		+	
Adhesive grouting compounds as backin	g for plaster	-	+
Tile adhesive		+	-
Pointing mortar		+	+
Joint cements		-	+
Adhesive grouting compounds as backing for tiles	or panels/	-	+
2-component sealing grouting compoun	ds		+
Leveling compounds		-	+
2-component epoxy-resin and sand mix		+	
Heat-insulating cement		+	-
High-performance mortar (Flowstone)		+	-
Plastic-modified mortar systems (PCC/ECC)		+	-
Steel fiber mortar		+	-
+=	suitable	- = unsu	vitable



Your Collomix dealer:

Collomix Rühr- und Mischgeräte GmbH • Daimlerstr. 9 • 85080 Gaimersheim