
Product data sheet

Status: 28.02.2019 | 21:02

Item no.37322





Designation	Composite corner bead "Mid-Flex 300" for dry lining Paper faced, roll
Description	Flexible, paper-concealed composite profile. The profile of the role will get the desired angular positon by creasing on the reset-free Superflex joint splint. It's situable for inside and outside edges. The roll material in a handy packaging allows an individual adjustment of the profile to the edge and thus reduces waste and costs. The embossed, ca. 13 mm wide paper wings at the ends of the legs allow an easier binding and running out of the putty, a faster drying process and a very good filler binding. The embossing also ensures an uniform paper support and offers a maximum adhesion without waviness or blistering. Inaccurate cut edges or offset joints can be concealed and don't have to be covered up separately.
Line of Business	Plaster
Productclass	Composite profiles
Productgroup	Profiles
Plaster thickness	1,0 mm
Product length	3050 cm
Product width	76 mm
Packaging Unit	10 PC / 24 CAR
Application Areas	For the use on gypsum plasterboards in the drywall construction, for the production of straight and precise inside and outside edges. The PVC core provides exceptional edge strength and durability, even in high traffic and busy areas. The paper-laminated composite profile is therefore particularly suitable for the restoration of chipped and dented edges.
Underground	The underground has to be sustainable, solid, clean and dry.
Revision	Putty the paper wing, the remaining profile leg doesn't have to be puttied over completely.
Consumption	The rolled products can be cut on the individual length of the edge on the object and reduce by this waste and costs. The consumption of filling compound depends on the structure of the surface and the absorbency of the underground as well as the qualities of the filling compound. Compared to conventional filler profiles, the material input becomes reduced.
Tool	For the efficient adjustment of the profile edge, the Flex-Folder 1479 is recommended. An optimal and efficient treatment is able by the material feeders Mud-Pro MP2 1472. For ensuring an optimal contact pressure, use the outside edge roller OSR 1473 or the inside edge roller ISR 1477.

PROTEKTORWERK

Florenz Maisch GmbH & Co. KG Postfach 1420, D-76554 Gaggenau Viktoriastr. 58, D-76571 Gaggenau Tel. +49 7225 977 - 0 Fax +49 7225 9 77 - 111 info@protektor.com www.protektor.com



Product data sheet

Status: 28.02.2019 | 21:02

Item no.37322

Storage

Store it cold, dry and protected from moisture.

Commentaires / characteristics

Inserting full-surface in the filling compound like conventional profiles with the printed side facing out. Filling the embossed paper wing in, the remaining profile leg doesn't need to be filled full-surface over.

Please notice the treatment note in the technical datasheets!

Notice the additional treatment notes and the datasheets of the used filling compound.

Material applicator Mud-Pro 1472, folding tool Flex-Folder 1479, outside edge roller WSR 1474, inside edge roller ISR 1477, extension rod EP 1478

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general. Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!



Florenz Maisch GmbH & Co. KG Postfach 1420, D-76554 Gaggenau Viktoriastr. 58, D-76571 Gaggenau Tel. +49 7225 977 - 0 Fax +49 7225 9 77 - 111 info@protektor.com www.protektor.com

