


CSK head, PZ, blue zinc-plated, full thread



BUILDING MATERIALS

- Glued-laminated timber
- Cross-laminated timber
- Laminated veneer plywood panels (e.g. Multiplex)
- Hard woods (pre-drilled)
- Chipboards and oriented strand boards (e.g. OSB panels)
- Plywood
- Solid wood panels
- Soft woods
- And many other wood materials

ADVANTAGES/BENEFITS

- The unique Power-Fast thread reaches into the screw tip and ensures a fast bite. This makes your work noticeably easier with all wood materials.
- The shank ribs (for screws with partial thread from 50 mm in length and up) substantially reduce drive-in resistance and thus enable greater power and battery conservation in your work.
- The optimised head geometry enables an exact and splinter-free surface finish without the screw twisting off, even with connections close to the edge.
- The ETA approval guarantees the high safety standard and the premium quality of fischer Power-Fast screws.

APPLICATIONS

- General wood joints
- Finger tightening elements
- Safety-relevant applications
- Plankings
- Skirting
- Door and metal fittings


APPROVALS



FUNCTIONING

- Screws with partial threads can lock wood parts into place by tightening them against each other.
- Full-thread screws are recommended for mounting thin parts and in less firm wood materials (e.g. soft woods).
- Screws with countersunk head can be flush mounted with the wood.
- Pan-Head screws are particularly well suited for metal and wood joints.
- The raised countersunk head is particularly suitable for joints where the screw head is visible and needs to leave behind an attractive appearance.

TECHNICAL DATA



FPF-SZ ZPF

Diameter 2,5

Diameter d [mm]	Length l [mm]	Drive	Art.-No. Art.-No.	Article name	ETA-approval	Full thread length l _g [mm]	Sales unit [pcs]
2,5	12	PZ1	652005	FPF-SZ 2,5 x 12 ZPF 200		9	200
2,5	16	PZ1	652008	FPF-SZ 2,5 x 16 ZPF 200		13	200
2,5	20	PZ1	652011	FPF-SZ 2,5 x 20 ZPF 200		17	200
3,0	12	PZ1	652020	FPF-SZ 3,0 x 12 ZPF 200		8	200
3,0	12	PZ1	652021	FPF-SZ 3,0 x 12 ZPF 500		8	500

Diameter 3,0

Diameter d [mm]	Length l [mm]	Drive	Art.-No.	Article name	ETA-approval	Full thread length l _g [mm]	Sales unit [pcs]
3,0	16	PZ1	652025	FPF-SZ 3,0 x 16 ZPF 200		12	200
3,0	16	PZ1	652026	FPF-SZ 3,0 x 16 ZPF 1000		12	1000
3,0	20	PZ1	652031	FPF-SZ 3,0 x 20 ZPF 200		16	200
3,0	20	PZ1	652032	FPF-SZ 3,0 x 20 ZPF 1000		16	1000
3,0	25	PZ1	652034	FPF-SZ 3,0 x 25 ZPF 200	■	21	200
3,0	25	PZ1	652035	FPF-SZ 3,0 x 25 ZPF 1000	■	21	1000
3,0	30	PZ1	652037	FPF-SZ 3,0 x 30 ZPF 200	■	26	200
3,0	30	PZ1	652038	FPF-SZ 3,0 x 30 ZPF 1000	■	26	1000
3,0	35	PZ1	652040	FPF-SZ 3,0 x 35 ZPF 200	■	31	200

Diameter 3,5

Diameter d [mm]	Length l [mm]	Drive	Art.-No.	Article name	ETA-approval	Full thread length l _g [mm]	Sales unit [pcs]
3,5	12	PZ2	652053	FPF-SZ 3,5 x 12 ZPF 200		8	200
3,5	12	PZ2	652054	FPF-SZ 3,5 x 12 ZPF 1000		8	1000
3,5	16	PZ2	652058	FPF-SZ 3,5 x 16 ZPF 200		12	200
3,5	16	PZ2	652059	FPF-SZ 3,5 x 16 ZPF 1000		12	1000
3,5	20	PZ2	652062	FPF-SZ 3,5 x 20 ZPF 200	■	16	200
3,5	20	PZ2	652063	FPF-SZ 3,5 x 20 ZPF 1000	■	16	1000
3,5	25	PZ2	652065	FPF-SZ 3,5 x 25 ZPF 200	■	21	200
3,5	25	PZ2	652066	FPF-SZ 3,5 x 25 ZPF 1000	■	21	1000
3,5	30	PZ2	652068	FPF-SZ 3,5 x 30 ZPF 200	■	26	200
3,5	30	PZ2	652069	FPF-SZ 3,5 x 30 ZPF 1000	■	26	1000
3,5	35	PZ2	652073	FPF-SZ 3,5 x 35 ZPF 200	■	31	200
3,5	35	PZ2	652074	FPF-SZ 3,5 x 35 ZPF 1000	■	31	1000

Diameter 4,0

Diameter d [mm]	Length l [mm]	Drive	Art.-No.	Article name	ETA-approval	Full thread length l _g [mm]	Sales unit [pcs]
4,0	16	PZ2	652097	FPF-SZ 4,0 x 16 ZPF 200		11	200
4,0	16	PZ2	652098	FPF-SZ 4,0 x 16 ZPF 1000		11	1000
4,0	20	PZ2	652102	FPF-SZ 4,0 x 20 ZPF 200		15	200
4,0	20	PZ2	652103	FPF-SZ 4,0 x 20 ZPF 1000		15	1000
4,0	25	PZ2	652104	FPF-SZ 4,0 x 25 ZPF 200	■	20	200
4,0	25	PZ2	652105	FPF-SZ 4,0 x 25 ZPF 1000	■	20	1000
4,0	30	PZ2	652106	FPF-SZ 4,0 x 30 ZPF 200	■	25	200
4,0	30	PZ2	652107	FPF-SZ 4,0 x 30 ZPF 1000	■	25	1000
4,0	35	PZ2	652111	FPF-SZ 4,0 x 35 ZPF 200	■	30	200
4,0	35	PZ2	652112	FPF-SZ 4,0 x 35 ZPF 1000	■	30	1000
4,0	40	PZ2	652116	FPF-SZ 4,0 x 40 ZPF 200	■	35	200
4,0	40	PZ2	652117	FPF-SZ 4,0 x 40 ZPF 1000	■	35	1000
4,0	45	PZ2	652121	FPF-SZ 4,0 x 45 ZPF 200	■	40	200
4,0	45	PZ2	652122	FPF-SZ 4,0 x 45 ZPF 500	■	40	500
4,0	50	PZ2	652126	FPF-SZ 4,0 x 50 ZPF 200	■	45	200
4,0	50	PZ2	652127	FPF-SZ 4,0 x 50 ZPF 500	■	45	500
4,0	60	PZ2	652840	FPF-SZ 4,0 x 60 ZPF 200		55	200

Diameter 4,5

Diameter d	Length l	Drive	Art.-No.		ETA-approval	Full thread length l _g	Sales unit
[mm]	[mm]		Art.-No.	Article name		[mm]	[pcs]
4,5	16	PZ2	652140	FPF-SZ 4,5 x 16 ZPF 200		11	200
4,5	16	PZ2	652141	FPF-SZ 4,5 x 16 ZPF 1000		11	1000
4,5	20	PZ2	652143	FPF-SZ 4,5 x 20 ZPF 200		15	200
4,5	20	PZ2	652144	FPF-SZ 4,5 x 20 ZPF 1000		15	1000
4,5	25	PZ2	652146	FPF-SZ 4,5 x 25 ZPF 200	■	20	200
4,5	25	PZ2	652147	FPF-SZ 4,5 x 25 ZPF 1000	■	20	1000
4,5	30	PZ2	652149	FPF-SZ 4,5 x 30 ZPF 200	■	25	200
4,5	30	PZ2	652150	FPF-SZ 4,5 x 30 ZPF 1000	■	25	1000
4,5	35	PZ2	652154	FPF-SZ 4,5 x 35 ZPF 200	■	30	200
4,5	35	PZ2	652155	FPF-SZ 4,5 x 35 ZPF 500	■	30	500
4,5	40	PZ2	652159	FPF-SZ 4,5 x 40 ZPF 200	■	35	200
4,5	40	PZ2	652160	FPF-SZ 4,5 x 40 ZPF 500	■	35	500
4,5	45	PZ2	652164	FPF-SZ 4,5 x 45 ZPF 200	■	40	200
4,5	45	PZ2	652165	FPF-SZ 4,5 x 45 ZPF 500	■	40	500
4,5	50	PZ2	652169	FPF-SZ 4,5 x 50 ZPF 200	■	45	200
4,5	50	PZ2	652170	FPF-SZ 4,5 x 50 ZPF 500	■	45	500
4,5	60	PZ2	652841	FPF-SZ 4,5 x 60 ZPF 200		55	200

Diameter 5,0

Diameter d [mm]	Length l [mm]	Drive	Art.-No.	Article name	ETA-approval	Full thread length l _g [mm]	Sales unit [pcs]
5,0	20	PZ2	652188	FPF-SZ 5,0 x 20 ZPF 200		14	200
5,0	20	PZ2	652189	FPF-SZ 5,0 x 20 ZPF 500		14	500
5,0	25	PZ2	652191	FPF-SZ 5,0 x 25 ZPF 200		19	200
5,0	25	PZ2	652192	FPF-SZ 5,0 x 25 ZPF 500		19	500
5,0	30	PZ2	652194	FPF-SZ 5,0 x 30 ZPF 200	■	24	200
5,0	30	PZ2	652195	FPF-SZ 5,0 x 30 ZPF 500	■	24	500
5,0	35	PZ2	652197	FPF-SZ 5,0 x 35 ZPF 200	■	29	200
5,0	35	PZ2	652198	FPF-SZ 5,0 x 35 ZPF 500	■	29	500
5,0	40	PZ2	652200	FPF-SZ 5,0 x 40 ZPF 200	■	34	200
5,0	40	PZ2	652201	FPF-SZ 5,0 x 40 ZPF 500	■	34	500
5,0	50	PZ2	652210	FPF-SZ 5,0 x 50 ZPF 200	■	44	200
5,0	60	PZ2	652217	FPF-SZ 5,0 x 60 ZPF 100		54	100
5,0	60	PZ2	652218	FPF-SZ 5,0 x 60 ZPF 500		54	500

Diameter 6,0

Diameter d [mm]	Length l [mm]	Drive	Art.-No. Art.-No.	Article name	ETA-approval	Full thread length l _g [mm]	Sales unit [pcs]
6,0	40	PZ3	652239	FPF-SZ 6,0 x 40 ZPF 200	■	34	200
6,0	50	PZ3	652246	FPF-SZ 6,0 x 50 ZPF 100	■	44	100
6,0	50	PZ3	652247	FPF-SZ 6,0 x 50 ZPF 400	■	44	400
6,0	60	PZ3	652251	FPF-SZ 6,0 x 60 ZPF 100	■	54	100
6,0	60	PZ3	652252	FPF-SZ 6,0 x 60 ZPF 200	■	54	200