

	ALBAU LTD	V 01
	Product technical data sheet	v1
		Page 1
		Pages 1

IFA P 065 MW / Mineral wool cap MW for flush installation

Post-installed mineral wool cap reduces heat transmission and results in a homogenous insulation surface



Applications:

- Mineral wool (MW) boards

Features and benefits:

- Cost-saving solution, as countersunk installation allows selection of shorter fixings.
- Results in homogeneous and smooth insulation surface
- Post-installed cap reduces heat transmission at fixing points

Technical data:

Product code	EAN	Material	Diameter	Package
ALB-IFA/P-065-MW	4751023402949	Mineral wool	65 mm	100 pcs.

Installation guide:

- Pre-assemble TFIX-8S-SETTING DEVICE with TFIX-8S fixing and then make installation of screw fixing
- Drill a hole of required diameter and depth
- Lightly tap the plastic sleeve through the insulation material into hole with a hammer, until fixing depth is reached
- When using the TFIX-DEVICE the teeth should be embedded in the insulation material after hammering.
- Tighten screw (using special TFIX-8ST-TOOL setting tool) until fixing is secure and flush with insulation material
- Embedment depth of min 25mm in A,B,C,D materials and 65mm in Aerated Concrete Block
- Drilling depth of min 40mm in A,B,C,D materials and 80mm in Aerated Concrete Block
- Insert cap into countersunk hole in insulation.

MADE IN EUROPE

Distributor: Ltd "Albau" – Ritvari, Rumbula, Stopinu district, LV-2121, Latvia. Reg.No. – 40103561205



www.albau.eu . www.xbau.eu.

