

## **ALBAU SIA**

# Technical data sheet


# **SHADOW-GAP PROFILE**

UV and alkali resistant shadow-gap profile for shadow joints in drywall constructions





| Brand                  | Albau                         |  |  |
|------------------------|-------------------------------|--|--|
| Profile material       | PVC – alkali and UV resistant |  |  |
| Profile length         | 2500 mm                       |  |  |
| Joint width            | 10 – 12 mm                    |  |  |
| Plasterboard thickness | 12,5 mm                       |  |  |
| Other dimensions       | See the scheme                |  |  |
| Profile color          | White                         |  |  |



#### **Features:**

- Aesthetically pleasing detail
- Connection between plasterboards and walls without cracks
- Simple and quick application
- Soft lip for accommodation to any wall surface
- For plasterboards with the thickness of 12,5 mm

### **Application:**

- Fix the bead to a plasterboard using staples or adhesive
- Apply the plaster and finish it at the protruding edge of the bead
- The recommended width of the joint is 10-12 mm

## Packaging, storage and transport:

- Packed in carton boxes
- Store in a dry roofed place
- Transport and store in horizontal position

### **Certifications and marks:**

The product is not subject to any harmonized standard

| Product code  | EAN           | Profiles in transport package, pcs. | Profiles on pallet, pcs. |
|---------------|---------------|-------------------------------------|--------------------------|
| ALB-SH-PVC-25 | 4752265005578 | 50 (125m)                           | 3200 (8000m)             |